



DATASHEET

GripFactory Antislip Aqua Tape

GripFactory Anti-Slip Aqua Tape is the solution to provide the bathroom, shower, pool or boat with an anti-slip strip and is very suitable for walking with bare feet. GripFactory Anti-Slip Aqua Tape is available in standard widths of 25 or 50 mm, on rolls of 18 meters or in squares of 140 x 140 mm. GripFactory Anti-Slip Aqua Tape is available from stock and available in various colors (black, white, grey, beige & transparent).

How does it work?

GripFactory Anti-Slip Aqua Tape is very easy to apply yourself. Due to the special surface structure, this anti-slip tape has an extremely high anti-slip value but is still very clean to keep, there are no lint from mop or cleaning cloth to the material.

Benefits

With GripFactory Anti-Slip Aqua Tape you are assured of a long-term solution against sliding surfaces. Because of the structure, aquaplaning has no chance and the ground feels comfortable enough to stand up with bare feet.

- Hygienic
- Easy to apply
- Removable
- Sustainable
- Cut to size yourself
- No tripping hazard

Areas of application

- Swimming pools
- Showers
- Bathrooms
- Bathtubs
- Toilets
- Saunas
- Boats and water sports facilities
- Surfboards

Suitable for the following surfaces

- Acrylic & Polyester
- Ceramic Tiles
- Marble & Granite
- Polyester
- Porselain & Enamel

GripFactory B.V.

Industrieweg 4 H
3442 AE Woerden
The Netherlands

☎ +31 (0)348 - 20 30 00

✉ info@gripfactory.nl

🌐 www.gripfactoryantislip.com

Technical data

Subject	Result	Test method
Back carrier	0.65 mm PVC	Caliper method
Type of adhesive	Modified solvent acrylic	n/a
Adhesive thickness	0.06 mm	n/a
Total thickness	0.71 mm	n/a
Initial tack (kg / 25.4 mm)	3.2	PSTC-16
Holding power	>24 hour	PSTC-7
Peel adhesion (N / 20 mm)	18.8	180° FINAT FTM1
Tensile strength (N / 20 mm)	< 200	Lloyd, 500 N load cell
Peel adhesion (kg / 25.4 mm)	1.4	PSTC-1
Tensile strength MD (kgf / cm ²)	120.4	ASTM D882A:1997
Elongation at break	199%	ASTM D882A:1997
Tear resistance (kgf / cm ²)	5.36	ASTM D1004:1994-DIE C
Dimensional stability	0%	ASTM D1593:1944
Temperature range (C)	-30 to +70 degrees C	n/a

Colors and light reflection values (LRV)

Color	PMS / RAL	LRV (av.)	LRV (range)
Beige	452C/1035	37.5	1
Black	-	4	4
Transparent	-	56	2
Grey	Cool grey 10/7037	10	2
White	-	82	2

Friction coefficient

Test standard	Dry surface	Wet surface
Pendulum	106 4S	31 4S
DIN 51097	Category B	



GRIPFACTORY

INNOVATIVE ANTI-SLIP PRODUCTS FOR EVERY SURFACE



GRIPFACTORY APPLICATION SERVICE

Are you unable to find a solution or do you have questions? Then contact the GripFactory Service Desk (+31 348-203000). For an additional cost you can have GripFactory Anti-Slip Aqua Tape applied by a certified applicator.